



## MAINTENANCE OIL

Ideal for refreshing and maintaining Polyx®-Oil surfaces.



3079 Clear  
Matt



3081 Clear  
Satin



3098 Clear  
Semi-Matt/  
Anti-Slip (R9)



3440 White  
Transparent



### PRODUCT DESCRIPTION

Clear or transparent, fast drying wood finish for the initial and routine care of oiled/waxed wooden floors. Dull and matt flooring is refreshed with Osmo Maintenance Oil. By applying Maintenance Oil at the right time, time-consuming sanding works and renovation can be avoided. Also suitable for changing the gloss level of intact surfaces treated with Osmo Polyx®-Oil.

Suitable for wood; microporous surface will not crack, peel, flake or blister. Resistant against wine, beer, cola, coffee, tea, fruit juice, milk and water in accordance with German DIN 68861-1A – no water spots. The dry finish is safe for humans, animals and plants (resistant to saliva and perspiration acc. German DIN 53160, suitable for children's toys acc. EN 71.3).

### RECOMMENDED USE

Osmo Maintenance Oil is ideal for the maintenance of all wooden flooring treated with Polyx®-Oil, such as solid wood, plank, parquet, strip, OSB and cork flooring, as well as stairs and furniture surfaces. Highly recommended for public interiors (e.g. restaurants, museums and other high traffic floors).

### INGREDIENTS

Based on natural plant oils and waxes (sunflower oil, soya oil, thistle oil, carnauba wax and candelilla wax), paraffin, titanium dioxide white pigment, siccatives (drying agents) and water-repellent additives. Deaeromatized white spirit (benzene-free). VOC classification in compliance with EU regulations (2004/42/EC): out of scope. Detailed declaration of ingredients available upon request.

### TECHNICAL DATA

Specific gravity: 0.85-0.95 g/cm<sup>3</sup>  
Viscosity: 40-60s DIN 53211/3 mm  
Odour: faint/mild, after drying odourless  
Flash point: >60°C acc. DIN EN ISO 2719

### STORAGE

Up to 5 years and longer if can is kept dry and closed tightly. If thickened by frost, store for 24-36 hours at room temperature before use.

### SURFACE PREPARATION

Wood surface must be clean, dry (moisture content max. 18 %) and free of dust.

Osmo Maintenance Oil is ready to use. Do not thin. Stir well before use.

Clean the surface thoroughly with Osmo Intensive Cleaner and rinse (damp mop) with clear water.

The finished surface is influenced by several factors, including the condition of the wood. Therefore, a trial application is always required, especially for unfamiliar surfaces.

### METHODS OF APPLICATION

With Osmo Double Blade Scraper or Osmo Microfibre Roller, apply thinly and evenly to the clean and dry wood along the wood grain and rub into the wood with a white pad (do not rub in 3098). Remove excess product.

For smaller areas, Osmo Maintenance Oil can be applied with a lint-free cloth.

Allow for good ventilation while drying.

### CLEANING OF TOOLS

With Osmo Brush Cleaner (free of aromatic compounds).



## DRYING TIME

Approx. 3-4 hours (normal climatic conditions, 23 °C/ 50 % rel. humidity). Lower temperatures and/or higher air humidity can increase the drying time. Ventilate well while drying.

## COVERAGE

1 litre covers approx. 40-60 m<sup>2</sup> with one coat. Coverage depends significantly on the condition of the wood. All information refers to smooth and planed/sanded surfaces. Other surfaces may lead to differences in coverage.

## NOTE

The maintenance results are influenced by several factors, including the condition of wood. Therefore, a trial application is always required.

If wood is raw or already greyed, the surface must be sanded and treated with Osmo Polyx<sup>®</sup>-Oil. Do not rub in Maintenance Oil 3098 Semi-Matt/Anti-Slip with a single disc machine.

## CAUTION

Keep out of reach of children. Do not get in eyes, on skin, or on clothing. If medical advice is needed, have product container or label at hand. Use only outdoors or in a well-ventilated area. Warning: Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition). The dried finish is classified as B2 (normal flammability) according to DIN 4102 regulations. Safety data sheet available on request.

## DISPOSAL

Dispose of leftover product and completely emptied packaging according to local official guidelines (waste code number 08 01 11). Only completely emptied cans can be recycled.

## COLOUR TONES

3079 Clear Matt  
3081 Clear Satin  
3098 Clear Semi-Matt/Anti-Slip (R9)  
3440 White Transparent

## CAN SIZES

0.20 L; 1 L; 2.50 L; 10 L;  
0.20 L (SET)

The above mentioned information is provided to the best of our knowledge however without any liability.

Version 02/18